

nmc

KWIK FINGER REPAIR CLAMP

FEATURES & BENEFITS

- Single wrap around design and varied bolt lengths allow for quick and easy installation
- Female and male bosses available to take off supply
- Stainless steel and mild steel versions
- Available with EPDM or Nitrile gaskets
- Available in length of 200mm and multiples of it
- Suitable for steel, spun iron, cast iron, ductile iron or asbestos cement pipe.
- Waffle Gaskets resist climatic conditions, petrol, oil, gas and water.
- Gasket Cemented in correct position for ease of installation.
- Gasket approved for use with potable water.
- Self-stabilizing finger brackets to prevent bolt bending.
- Corrosion proof.

MATERIAL SPECIFICATION

- Body - Stainless steel SS304 (SS316 available on request)
- Lugs / Clamps - SG iron BS EN 1563:1997, IS 1865:2000 (Fusion bonded Epoxy coated)
- Bolts, Nuts & Washers - Steel Zinc plated. Bolts grade 6.8
- Gasket - EPDM (Nitrile available on request)
- Torque on M16 bolts 95-136Nm (70-100lbf ft)



SINGLE SECTION 200MM LENGTH

Diameter Range		L=200 (3 Bolt)
Min	Max	Weight
mm	mm	Kg
48	54	3.6
56	62	3.7
60	66	3.8
68	74	3.8
78	88	3.9
88	98	4.0
98	108	4.1
108	118	4.1
114	124	4.2
126	136	4.3
138	150	4.4
140	153	4.4
150	162	4.4
162	174	4.5
168	182	4.6
174	186	4.7
186	198	4.8
198	210	4.9
210	223	4.9
222	234	5.0
234	246	5.1
243	255	5.2
260	272	5.2
273	285	5.4
285	297	5.4
298	310	5.5
316	328	5.6
327	340	5.8
342	355	5.9
353	365	6.0
368	380	6.1
378	390	6.2

DOULBE SECTION 200MM LENGTH

Diameter Range		L=200 (6 Bolt)
Min	Max	Weight
mm	mm	Kg
48	54	3.6
88	110	7.2
114	137	7.4
138	160	7.6
160	182	7.7
182	202	8.0
202	224	8.1
217	240	8.2
240	262	8.2
262	284	8.3
273	296	8.7
296	319	8.7
324	346	9.1
346	368	9.1
365	387	9.2
387	410	9.5
410	432	9.8
428	450	10.0
450	474	10.1
470	492	10.3
492	516	10.4

Standard Clamps

Sections	Diameter covered	Length available
	mm	mm
Single	390	200,400,600,800
Double	516	200,400,600,800,1000
Triple	1255	400,600,800,1000,1200

Note : Repair clamps for larger diameter, multiple sections and longer length are available on request

13/49/08

Nanda Millar Company

Office : 32A, Chittaranjan Avenue, 2nd Floor, Kolkata-700 012. India. Tel : +91 33 2212 3530 / 3531 / 1783
 Fax : +91 33 2212 2070. E-mail : nmc@nandagroup.com, nmcjp@hotmail.com. URL : www.nandagroup.com



An ISO 9001 : 2000
Registered Company